

JAH & JAS - ALUMINIUM JACKS



Capacities from 10 to 60 tonnes

Stroke lengths from 75 to 305mm

Internal safety overload device

The JAH and JAS ranges of lightweight aluminium jacks offers a wide variety of capacities and lift height options. Available as either plain ram lifting jacks, with or without “failsafe” mechanical lock ring, or optional low height claw lifting design, all models are constructed predominantly of lightweight aluminium alloy with all critical functioning parts manufactured from high quality steel. Used extensively in maintenance, construction, heavy plant and machinery applications, these high quality jacks are the proven industry standard.

- >> Lightweight construction
- >> Stroke limiting device
- >> Available as plain ram jack, claw jack or “failsafe” locking ring design

Model number	Jack capacity tonnes	Claw capacity tonnes	Stroke mm	Weight kg
Multi purpose superjack				
JAS103	10	-	75	4.3
JAS105	10	-	125	5.7
Jack with plain piston				
JAH620	20	-	152	11
JAH1220	20	-	305	17
JAH630	30	-	152	16
JAH1230	30	-	305	24
JAH660	60	-	152	28
JAH1260	60	-	305	44
Jack with plain piston & lifting claw & with extended base				
JAH620C	20	8	152	15
JAH1220C	20	8	305	23
JAH630C	30	12	152	21
JAH1230C	30	12	305	32
JAH660C	60	24	152	44
JAH1260C	60	24	305	65
Jack with “failsafe” locking ring				
JAH620SR	20	-	152	13
JAH1220SR	20	-	305	19
JAH630SR	30	-	152	17
JAH1230SR	30	-	305	25
JAH660SR	60	-	152	30
JAH1260SR	60	-	305	46

Dimensions in mm			
Closed height	Toe height	Base length	Base width
131	-	162	75
181	-	162	75
263	-	178	121
438	-	246	121
263	-	203	140
451	-	273	140
293	-	251	190
500	-	342	190
280	67	246	121
456	67	246	121
281	73	273	140
472	73	273	140
327	73	342	190
540	73	342	190
289	-	178	121
464	-	246	121
292	-	203	140
479	-	273	140
330	-	251	190
536	-	342	190

Note: JAS103 and JAS105 feature spring assisted piston retraction